


SFX/ECO-3C-6.0-EV-C5-FTP-LSZH-SWA-BLK

Eco EV 3 x 6mm plus Cat 5 FTP LSZH UV Armoured Black CPR:Eca



Cable Construction	Flex	Cat5e FTP
Conductor	Plain Annealed Class 2 Copper	Bare Copper
Conductor cross sectional area (mm2)	6.0mm²	
Insulation	XLPE	HDPE
Insulation Colour(s)	Brown;Blue;Green/Yellow	Bl/Wh/Bl;Or/Wh/Or;Grn/Wh/Grn;Br/Wh/Br
Foil Shield	N/A	>=115%
Bedding	LSZH	
Armour	Galvanised Steel	
Outer Jacket	LSZH UV Resistant	LSZH
Overall Diameter (mm)	18.6mm	6.10 ±0.30
Jacket Colour	Black RAL 9005	Black RAL 9005
Sheath Printing	ECO EV SWA 3 x 6mm + C5e FTP 300-500V (PO) (m)	
Reaction to Fire	Eca	
Electrical Characteristics		
Current Capacity in air (A)	58A	
Rated Temperature (°C)	-15°C to 90°C	
Min Bend Radius (mm)	8 x Ø	
Weight	700kg/km	
Application	EV charge points with data connectivity.	